


IR FIXED LENS DOME CAMERA

DI-340IP528
DI-340IP536



1/3" CMOS Sensor
4 Mega-Pixel
True Day & Night (IR Cut Removable)
H.265 (HEVC) Compression
0 Lux (IR On) Min. Illumination

ONVIF
True WDR / BLC / HLC
3D Noise Reduction
Motion Detection and Privacy Masking
2.8mm/3.6mm Mega-Pixel Lens

15m IR Illumination
PoE Support
1 Way Audio
CVBS
IP 66 Protection

Specifications

Camera	Video	Model	DI-340IP528	DI-340IP536	Housing	IR Distance	15m (2 High Power IR LED)		
		Image Sensor	1/3" CMOS			Lens	2.8mm (DI-340IP528)	3.6mm (DI-340IP536)	
		Effective Pixels	2688x1520			Iris	Fixed Iris		
		Electronic Shutter	1/25s ~ 1/100000s			Lens Mount	Φ14 mount		
		Frame Rate	Standard: 1-25/30 (True-WDR), HFR*: 1-50/60 (Max. 1080P & D-WDR)			Water-proof	IP66		
		Day & Night	ICR			Bracket	3-Axis Wall Bracket		
		Min. Illumination	0lux (IR ON)			Dimensions	Ø107mm×95mm		
		Audio	Audio compression	G.711A/G.711U		Weight(gross)	400g		
			Communication	One-way Audio		Connectivity	Network	RJ45 (+PoE)	
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable		Power		DC Socket		
			Image Enhancement	True WDR (HFR* Disabled) / BLC / HLC / ROI			Analog Video Output	CVBS (RCAx1)	
			Noise Reduction	3D-DNR			Mic Connectivity	1Ch Input	
		Image Orientation	Mirror/Flip		SD Card		No		
		Privacy Zone	Yes		RS485		No		
		Motion Detection	Yes		Alarm	No			
		Compression	Video Compression	H.265 / H.264		Network	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App	
			Resolution	4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240			User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission	
	Multi-stream		4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS / 1~50/60FPS with HFR*)		Network Protocol		TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP		
	Bit rate		64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264		ONVIF		Yes		
Encode Mode	VBR/CBR		Ethernet	100Mbps					
Image Quality	Five levels under VBR; Free adjustment under CBR		PoE	Yes					
Others					Power Supply	DC12V/~280mA / PoE/~4W			
					Work Environment	-30℃~50℃, 10%~90% Humidity			

*HFR (High Frame Rate) must be supported by the NVR in order to work properly.

