

LPR MVF LENS BULLET CAMERA

I6-320LPR-MVF
I8-320LPR-MVF



- 1/2.8" CMOS Sensor
- 2 Mega-Pixel
- True Day & Night (IR Cut Removable)
- H.265 (HEVC) Compression
- 0 Lux (IR On) Min. Illumination
- ONVIF
- True WDR
- 3D Noise Reduction
- Motion Detection and Privacy Masking
- AI Analytics (LPR)
- Audio Input + Output
- Alarm Input + Output
- 2.8-12mm / 9-22mm Motorized
- VF Lens with Auto Focus
- 60m / 80m IR Illumination
- PoE Support
- IP 67 Protection
- Micro SD Card Support
- Technician Port

Specifications

Camera	Model	I6-320IPE-MVF	I6-320IPE-MVF
		Video	1/2.8" CMOS (16:9)
	Image Sensor	1920x1080	
	Effective Pixels	1/25s ~ 1/100000s	
	Electronic Shutter	1-25/30FPS	
	Frame Rate	ICR	
	Day & Night	Day: 0.1lux / Night: 0.005lux (@F1.6, AGC On) 0lux with IR on	
	Min. Illumination	G.711A/G.711U	
	Audio compression	Two-way Audio	
	Communication	AWB, AGC Adjustable, Exposure Mode (Auto) Sharpness, Saturation, Brightness & Contrast Adjustable	
	Image Settings	True WDR (120dB), BLC, HLC, ROI	
	Image Enhancement	3D-DNR	
	Noise Reduction	Mirror/Flip	
	Image Orientation	Yes	
	Privacy Zone	Yes	
	Motion Detection	Yes	
	Analytics	LPR (License Plate Recognition). Detection Speed of 0-70Km/h Camera Tampering	
Compression	Video Compression	H.265S/H.264S*, H.265+/H.264+/H.265/H.264/MJPEG**	
	Resolution	2MP / 1MP / D1 (704x576) / QVGA (480x240) / CIF (352x288)	
	Multi-Stream	Master Stream: 2MP (1920x1080) / 1MP (1280x720) (1~30fps) Sub-Stream: 1MP/QVGA/D1/CIF	
	Bit rate	Third Stream: QVGA/D1/CIF (1~30fps) 64Kbps ~ 4Mbps@H.265 / 64Kbps ~ 6Mbps@H.264	
	Encode Mode	VBR/CBR	
	Image Quality	Five levels under VBR; Free adjustment under CBR	

Housing	IR Distance	60m (4 High Power IR LED)	80m (4 High Power IR LED)
	Lens (Field of View)	2.8-12mm MVF(103.4°-32.4°)	9-22mm MVF (44°-17.6°)
Iris	DC Iris		
Lens Mount	Ø14 Mount		
Protection Rate	Water Proof: IP67		
Bracket	3-Axis Wall Bracket		
Dimensions	279.5x88.9x100.3mm		
Weight(gross)	~1040g		
Connectivity	Network	RJ45 (+PoE)	
	Power	DC Socket	
	Analog Video Output	CVBS Out + Technician Port	
	Audio Connectivity	Audio Input + Audio Output	
	SD Card	Event/Schedule based Main/Sub-Stream recording (Up to 128Gb)	
Hard Reset Button	Yes		
Alarm	Alarm in + Alarm Out		
Network	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App	
	User Access	Supports simultaneous monitoring for up to 3 users with multi-stream real time transmission	
	Network Protocol	IPv4, IPv6, TCP, UDP, DHCP, NTP, DDNS, 802.1X, RTSP, Multicast, UPnP, Email, FTP, HTTPS, QoS	
ONVIF	Yes		
Ethernet	100Mbps		
PoE	Yes		
Others	Power Supply	DC12V/~910mA / PoE/~11W	
	Work Environment	-30°C~60°C, 10%~90% Humidity	

*Main Stream Only, **Sub-Streams Only

